



| Amigo Mobility Product specifications | Dex Pro+ <i>standing platform truck with releasable deck</i> | Dex Pro <i>standing platform carrier</i> | Dex HD <i>powered personnel mover HD</i> | Dex <i>powered personnel mover</i> | Max Pro <i>powered platform truck</i> |
|---------------------------------------|------------------------------------------------------------------------|----------------------------------------------------|----------------------------------------------------|----------------------------------------------|-------------------------------------------------|
| Weight capacity | Total capacity: 1,100 lbs (including rider) | Total capacity: 1,100 lbs (including rider) | Total capacity: 3,000 lbs (including rider) | Total capacity: 1,500 lbs (including rider) | Capacity: 1,100 lbs |
| Speed | 4 mph (programmable) | 4 mph (programmable) / 6 mph option | 4.6 mph (programmable) | 4 mph (programmable) / 6 mph option | 4 mph (programmable) |
| Peak Power | 858 watts/1.15 hp | 858 watts/1.15 hp | 600 watts/.80 hp | 858 watts/1.15 hp | 858 watts/1.15 hp |
| Battery life | 8 hours, 30+ miles | 8 hours, 30+ miles | 15 hours, 69+ miles | 8 hours, 30+ miles | 8 hours, 30+ miles |
| Battery | Two 12-volt/45 AH batteries | Two 12-volt/45 AH batteries | Two 12-volt/105 AH batteries | Two 12-volt/45 AH batteries | Two 12-volt/45 AH batteries |
| Charger DC output | 7 amp | 7 amp | 15 amp | 7 amp | 7 amp |
| Charger AC input | 1.5 amp, charges on 110v | 1.5 amp, charges on 110v | 4 amp | 1.5 amp, charges on 110v | 1.5 amp, charges on 110v |
| Overall dimensions | 95" L x 31.5" W x 62" H | 81" L x 26" W x 62" H | 53" L x 28" W x 82" H | 55" L x 26" W x 62" H | 54" L x 25.5" W x 47.5" H |
| Deck dimensions | 50" L x 30" W | 40" L x 22" W | N/A | hitch optional | 40" L x 22" W |
| Deck height | 14" from floor | 14" from floor | N/A | N/A | 14" from floor |
| Turning radius | 52.5" | 42.5" | 46" | 41.5" | 41.5" / zero-turn |
| Maximum incline rating | 6° (10.5%) at 50% load 4° (7%) at 100% load | 6° (10.5%) at 50% load 4° (7%) at 100% load | 4° (7%) at 75% load | 4° (7%) at 75% load | 6° (10.5%) at 50% load 4° (7%) at 100% load |
| Charging times | 7 hours @ recommended 50% DOD | 7 hours @ recommended 50% DOD | 7 hours @ recommended 50% DOD | 7 hours @ recommended 50% DOD | 7 hours @ recommended 50% DOD |
| Hour meter | Standard | Standard | Standard | Standard | Standard |
| Battery Indicator | 5 LED bars to show capacity | 5 LED bars to show capacity | 5 LED bars to show capacity | 5 LED bars to show capacity | 5 LED bars to show capacity |
| Tires | Rubber, solid foam filled | Rubber, solid foam filled | Polyurethane, 10" | Rubber, solid foam filled | Rubber, solid foam filled |
| Options | Side rails, netting, hitch, strobe light | Side rails, netting, strobe light | Hitch, basket, strobe light, Canopy | Hitch, basket, strobe light | Side rails, netting |

Amigo Mobility International, Inc.

6693 Dixie Highway • Bridgeport, MI USA • 989-777-0910 • carts@myamigo.com • myamigo.com/industrial

Improving Lives Through Mobility® since 1968